

Package ‘numspellR’

May 9, 2026

Title Detection of Numeric Persistence and Rigidity Patterns

Version 0.1.0

Description Tools for detecting numeric persistence (“`spells”) and rigidity patterns in time-ordered numeric data. The package identifies periods of stability, computes spell-based rigidity metrics, and provides plain-language interpretations suitable for policy and applied analysis.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 3.6.0)

Imports stats

Suggests testthat (>= 3.0.0), knitr, rmarkdown

RoxygenNote 7.3.3

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Joko Ade Nursiyono [aut, cre] (ORCID:
<<https://orcid.org/0009-0008-1179-6776>>)

Maintainer Joko Ade Nursiyono <jokoadenursiyono@gmail.com>

Repository CRAN

Date/Publication 2026-02-06 13:40:02 UTC

Contents

numspellr	2
Index	4

Description

numspellr() is a universal numeric persistence detector designed to identify prolonged stability ("spells") and rigidity patterns in numeric data. The function automatically detects numeric variables from various data structures (numeric vectors or data frames) and computes persistence metrics commonly used in rigidity and stickiness analysis.

The output includes interpretable measures such as average spell length, stability ratio, elasticity, and adjustment frequency, accompanied by plain-language interpretations suitable for policy and applied analysis.

Usage

```
numspellr(data, lang = c("indonesia", "english"), min_spell = 2, tol = NULL)
```

Arguments

data	A numeric vector or a data.frame/tibble containing one or more numeric variables. Non-numeric columns are ignored automatically.
lang	Language for persistence status labels and interpretation text. Must be either "indonesia" or "english".
min_spell	Minimum length (in periods) required for a sequence to be considered a persistence spell. Default is 2.
tol	Optional numeric tolerance threshold for detecting stability. If NULL (default), tolerance is determined automatically based on variability of first differences.

Details

The function identifies persistence spells as consecutive periods where absolute changes fall below a tolerance threshold.

Metrics computed include:

- **avg_spell**: average duration of stable periods.
- **median_spell**: median duration of stability.
- **max_spell**: longest observed stable period.
- **stability_ratio**: proportion of observations belonging to spells.
- **elasticity_index**: average relative magnitude of changes.
- **adjustment_frequency**: share of periods with meaningful changes.
- **spell_concentration**: dominance of long spells over short ones.

Persistence status is classified into qualitative categories ranging from highly flexible to highly rigid, with labels adapted to the selected language.

Value

A data.frame with one row per numeric variable containing:

structure Detected data structure type.

id Variable identifier.

variable Variable name.

avg_spell Average persistence spell length.

median_spell Median persistence spell length.

max_spell Maximum persistence spell length.

stability_ratio Share of observations in stable spells.

elasticity_index Average relative change magnitude.

adjustment_frequency Frequency of meaningful adjustments.

spell_concentration Concentration index of persistence spells.

persistence_status Qualitative persistence category.

interpretation Plain-language interpretation suitable for policy analysis.

Author(s)

Joko Nursiyono

References

Caballero, R. J., & Engel, E. M. R. A. (1993). Microeconomic adjustment hazards and aggregate dynamics. *Quarterly Journal of Economics*, 108(2), 359–383.

Nakamura, E., & Steinsson, J. (2008). Five facts about prices: A reevaluation of menu cost models. *Quarterly Journal of Economics*, 123(4), 1415–1464.

See Also

[diff](#), [rle](#)

Examples

```
x <- c(10, 10, 10, 11, 11, 11, 11, 12)
numspellr(x, lang = "english")
```

```
df <- data.frame(
  time = 1:8,
  value = c(5, 5, 5, 5, 6, 6, 6, 7)
)
numspellr(df, lang = "indonesia")
```

Index

diff, 3

numspellr, 2

rle, 3